

### Features & Benefits

- Internal Driver
- Smooth, Consistent Light
- UL for Safety
- No UV, No Mercury
- Long Life
- High CRI
- Instant on, no delay or warm up time
- Convenient and quick installation
- Input from Both Ends
- Utilizes shunted or unshunted G13 sockets
- Compatible with controls and sensors
- Works in cold temperature applications
- Glass tube for superior optical performance
- 5 Year Warranty
- Superior Wide View Angle



Internal Driver **LED Lamp**  
**Double End Input**



**Flex™**  
Internal Driver LED Lamp

### Specification Data

Model No.	Length	Base type	Lamp Wattage	Input Voltage	CCT	Initial Lumens	CRI	Beam Angle	LPW	Power Factor	THD	DLC
L24T8/835/9G-ID DE	24	G13	9	120/277	3500K	1100	83	325	120	0.9	<20%	Yes
L24T8/840/9G-ID DE	24	G13	9	120/277	4000K	1100	83	325	120	0.9	<20%	Yes
L24T8/850/9G-ID DE	24	G13	9	120/277	5000K	1100	83	325	120	0.9	<20%	Yes
L24T8/830/9G-ID DE	24	G13	9	120/277	3000K	1100	83	325	120	0.9	<20%	Yes
L24T8/845/9G-ID DE	24	G13	9	120/277	4500K	1100	83	325	120	0.9	<20%	Yes

### Ordering Information

EXAMPLE: **L48T8/840/14G-ID DE**

**L**

Manufacturer's Code

**48**

Normal Length  
48=48"

**T8**

Lamp Shape  
T8=T8

**8**

CRI  
8 =>80

**40**

CCT  
50 =5000K  
40 =4000K  
35 =3500K

**14 G**

Wattage  
14G-14W

- **ID**

Internal Driver

**DE**

Double End Input

## Features & Benefits

- Internal Driver
- Smooth, Consistent Light
- UL for Safety
- No UV, No Mercury
- Long Life
- High CRI
- Instant on, no delay or warm up time
- Convenient and quick installation
- Input from Both Ends
- Utilizes shunted or unshunted G13 sockets
- Compatible with controls and sensors
- Works in cold temperature applications
- Glass tube for superior optical performance
- 5 Year Warranty
- Superior Wide View Angle



Internal Driver **LED Lamp**  
**Double End Input**



**Flex™**  
Internal Driver LED Lamp

## Specification Data

Model No.	Length	Base type	Lamp Wattage	Input Voltage	CCT	Initial Lumens	CRI	Beam Angle	LPW	Power Factor	THD	DLC
L36T8/835/12G-ID DE	36	G13	12	120/277	3500K	1400	83	325	120	0.9	<20%	No
L36T8/840/12G-ID DE	36	G13	12	120/277	4000K	1400	83	325	120	0.9	<20%	No
L36T8/850/12G-ID DE	36	G13	12	120/277	5000K	1400	83	325	120	0.9	<20%	No

## Ordering Information

EXAMPLE: **L48T8/840/14G-ID DE**

<b>L</b>	<b>48</b>	<b>T8</b>	<b>8</b>	<b>40</b>	<b>14 G</b>	-	<b>ID</b>	<b>DE</b>
Manufacturer's Code	Normal Length 48=48"	Lamp Shape T8=T8	CRI 8 =>80	CCT 50 =5000K 40 =4000K 35 =3500K	Wattage 14G-14W		Internal Driver	Double End Input