

Features & Benefits

- Internal Driver
- Smooth, Consistent Light
- UL for Safety
- No UV, No Mercury
- Long Life
- High CRI
- Instant on, no delay or warm up time
- Convenient and quick installation
- Input from Both Ends
- Utilizes shunted or unshunted G13 sockets
- Compatible with controls and sensors
- Works in cold temperature applications
- Glass tube for superior optical performance
- 5 Year Warranty
- Superior Wide View Angle



Internal Driver **LED Lamp**
Double End Input



Flex™
Internal Driver LED Lamp

Specification Data

Model No.	Length	Base type	Lamp Wattage	Input Voltage	CCT	Initial Lumens	CRI	Beam Angle	LPW	Power Factor	THD	DLC
L48T8/835/17G-ID DE	48	G13	17	120/277	3500K	2200	83	325	120	0.9	<20%	Yes
L48T8/840/17G-ID DE	48	G13	17	120/277	4000K	2200	83	325	120	0.9	<20%	Yes
L48T8/850/17G-ID DE	48	G13	17	120/277	5000K	2200	83	325	120	0.9	<20%	Yes
L48T8/830/17G-ID DE	48	G13	17	120/277	3000K	2200	83	325	120	0.9	<20%	Yes
L48T8/845/17G-ID DE	48	G13	17	120/277	4500K	2200	83	325	120	0.9	<20%	Yes

Ordering Information

EXAMPLE: **L48T8/840/14G-ID DE**

L

Manufacturer's Code

48

Normal Length
48=48"

T8

Lamp Shape
T8=T8

8

CRI
8 =>80

40

CCT
50 =5000K
40 =4000K
35 =3500K

14 G

Wattage
14G-14W

- **ID**

Internal Driver

DE

Double End Input