ONCE®





Junction Box Format

- Improves the welfare of your animal
- Dim-to-Calm[™] technology
- Advanced system specialized for Swine
- 10 W LED equivalent to 75 W incandescent
- Energy provider rebates, DLC approved
- Fully dimmable daylight and nighttime modes
- Replaces CFL screw-base lamps
- Low-profile, wide beam angle
- Patented spectral output[†]
- Built For Your Barn® design



AgriShift® lighting systems are agriculture specific and developed to meet the individual needs of your animals†. The lights "shift" spectrum and intensity.



Dim-to-Calm™ technology simulates sunrise and sunset and can act as "service light" when fully dimmed.



ONCE® AgriShift® fixtures have a Built For Your Barn® design, using techniques and materials that withstand the harsh barn environment for years to come.

Animal-Centric Lighting Systems

The AgriShift® MLM-S is a highly efficient fixture designed to provide exceptional light for both the swine herd and humans caring for them, while supporting the biosecurity of modern swine facilities. It is suitable for use in sow barns, gestation buildings, nurseries, gilt development units and finishing facilities.

This modular designed LED allows for easy installation and can replace existing CFL fluorescent bulbs, eliminating constant replacement cycles.

The Science Behind the Technology

The AgriShift® MLM-S features swine specific Dim-to-Calm™ technology and a Built For Your Barn® design. It simulates sunrise and sunset which reduces stress on your animals caused by sudden changes in light. The dimming capability also allows the AgriShift® MLM-S to fully dim red, which swine perceive as darkness. This allows the red light to be used as "service light", allowing workers to access the facility without disturbing or interrupting the sleep cycles of the animal.



AgriShift® MLM-S Specifications

Nominal Power	10 W (at full intensity)
Luminous Flux (nominal)	1050 lm
Input Voltage	120 VAC / 60 Hz
Beam Angle	200°
Light Output Equivalence	Up to 75 W incandescent
Spectral Output	Swine specific full spectrum white
Operating Temperature	-20°C to 40°C / -4°F to 104°F
Dimmable Range	100% to 5%, dims to red-white moonlight
Dimmer Type	Phase Modulation or Amplitude Control***
Environmental Ratings	Suitable for wet locations (JB), ROHS Compliant,
	Suitable for damp locations
Safety	ETL Listed, Conforms to UL std. 1598 (JB)
	Certified to CAN/CSA C 22.2 No. 25008 (JJ)
	Conforms to UL Std. 1993 (JJ)
	Certified to CSA Std. C 22.2 No. 1993 (JJ)
Rated Life	50,000 hours
Limited Warranty	3 Years (24/7 operation)

Ordering Information

AgriShift* MLM-S 120V** MLM-SSWR-BU-180T-010-120

Jelly Jar Mount (JJ) MLM-SSWR-JJ-180T-010-120

Includes JJ adapter/connector kit

Junction Box Mount (JB) MLM-SSWR-JB-180T-010-120
Includes JB adapter/connector kit

AgriShift® MLM-S 230V SKU

Jelly Jar Mount (JJ) MLM-SSWR-JJ-180T-010-230

Includes JJ adapter/connector kit

Junction Box Mount (JB) MLM-SSWR-JB-180T-010-230

Includes JB adapter/connector kit


AgriShift® Controllers SKU


 Master Controller 120V
 LCL-0.2-120V / 30-014-00134


 Slave Dimmer 120V
 LCL-30-014-00156-L123


 Master Controller 240V
 LCL-0.2-240V / 30-014-00144

AgriShift® MLM-S Mechanical Dimensions









* Includes (4) stainless steel screws

** DLC approved product number. When submitting to your energy providers for rebates, use this product SKU.

*** For optimum dimming performance use AgriShift® Dimmer/Controller

AgriShift® Controllers Master and Slave Units

- Precise, consistent, incremental dimming
- Program up to 500 days divided into 20 lighting periods
- Advanced technology for LED lighting
- Daylight and night time modes
- Fully automatic control or manual options







Slave Dimmer

The integrated AgriShift® Master Controller and Slave Dimmer provide smooth, programmable dimming to enable the full potential of any ONCE® AgriShift® fixture. They offer several advanced features that address the complex needs of today's modern farming facilities and can both be easily programmed with the accessible display and program buttons on the front panel.

